Fuelfix & Tanks2Go 70,000L Self-Bunded Solar-Powered Tank

The Fuelfix Self-Bunded Solar 70FF couples a 5kW solar array with 10kwh battery to deliver a self-powered large scale fuel storage solution in a single footprint. This easy to move and setup system is ideal for remote location such as well mining and construction sites, requiring on-site refuelling.



The tank is capable of dispensing over 55,000 litres per day using solar energy, with an additional backup dispensing capacity of 20,000 litres from the battery. This system operates independently, requiring no external diesel generator, thereby reducing operational and maintenance costs.

Bo Movable - Single Footprint

This tank is easily transported using side-loaders or a tilt tray, removing the need for cranes, EWP's and any related working at height risks when loading and unloading. The tank is transported with the solar array attached in a retracted position which can then be easily deployed in minutes. The battery is securely housed within the enclosed bund.



Gross Capacity:	Height:
69,400L	3,251 mm
Safe Fill:	Length:
65,930L	12,180 mm
Weight (Empty):	Width:
14,050 kg	2,430 mm
Weight (Full Tank):	Design Standards:
69,853 kg	UL 142, ULCS601

Australian Standards: AS1940, AS1657, AS1692

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.

Standard Fittings

3" Male camlock coupling with dust cap fitted to tanker filling point, wafer non-return fitted to filling line, 3" fire safe ball valves, container corner castings, primary tank access manway, calibrated fluid level dipstick and statutory signage, interstitial space dip point. Finished in white marine grade polyurethane paint.

Optional Fittings

- Dispensing solutions from light vehicles to heavy vehicles.
- Fuelfix fuel management system.







Secure and Efficient

Overfill protection supplied with mechanical shut-off and alarm. Free-to-air vent weather cap. Tank floor has fall-tofront for water collection and tank-top evacuation point. Front mounted security doors with container lock.

Renvironment- Friendly

Fully solar powered eliminates noise and emissions. Self-bunded double wall design and spill contained pump bay housing with removable ventilation panels. Anti-syphon valve prevents fuel loss and possible contamination should a pipe or hose fail

¥= *	Safety

Anti-islanding feature only activates PV array when 230V is present on the output. Solar array rated to category A & B regions when panels extended and Cyclone when panel retracted.

द्भ	
٥þ	Flexibility

For customers requiring larger dispensing volumes, enhanced backup capabilities or specific requirements, this tank can be integrated with Fuelfix's extensive range of battery and hybrid power solutions. This allows Fuelfix to customise a solution tailored to the specific needs of each customer.

General - Solar Array



Model:	Power:	
S olar Skid 5.0kW	5.0kWp	
Voltage:	Current:	
230V	21.73A	
Panel:	Number of Panels:	
500W	10	
Mounting: Container – ISO Locks		
Wind Rating: Category A & B regions with panels extended, Cyclone when panels retracted.		

These specifications are subject to variation. Please contact the Fuelfix Sales team for more information.



